

ISO7-2:2000 and DIN EN 10226 GAUGES ISO7-2:2000 ve DIN EN 10226 MASTARLAR

ISO7-2:2000 and DIN EN 10226 PLUG GAUGE ISO7-2:2000 ve DIN EN 10226 TAMPON MASTAR

R ISO 7-2:2000 Taper / Konik	PITCH HATVE	CODE KOD	EURO
ISO7-2:2000 R 1/8"	28	MISO7R018E	212.00
ISO7-2:2000 R 1/4"	19	MISO7R014E	226.00
ISO7-2:2000 R 3/8"	19	MISO7R038E	243.00
ISO7-2:2000 R 1/2"	14	MISO7R012E	263.00
ISO7-2:2000 R 3/4"	14	MISO7R034E	295.00
ISO7-2:2000 R 1"	11	MISO7R100E	346.00
ISO7-2:2000 R 1-1/4"	11	MISO7R114E	413.00
ISO7-2:2000 R 1-1/2"	11	MISO7R112E	466.00
ISO7-2:2000 R 2"	11	MISO7R200E	571.00
ISO7-2:2000 R 2-1/2"	11	MISO7R212E	672.00
ISO7-2:2000 R 3"	11	MISO7R300E	800.00
ISO7-2:2000 R 4"	11	MISO7R400E	1.130.00

ISO7-2:2000 taper plug gauges have go and no go on one single side.
ISO7-2:2000 konik tampon mastarlarda geçer ve geçmez tek taraftadır.



Withworth taper pipe thread ISO7 and DIN EN10226 plug gauges are used for gauging ISO 7-1 or DIN EN 10226 Rp internal parallel and Rc internal taper thread.

Plug gauges are taper and they are marked as "ISO7 Rc/Rp No1"

Withworth konik boru dişi ISO7 ve DIN EN10226 tampon mastarlar ISO 7-1 veya DIN EN 10226 Rp düz iç vida ve Rc konik iç vida kontrolü için kullanılır. Tampon mastarlar koniktir "ISO7 Rc/Rp No1" olarak markalanmıştır

ISO7-2:2000 and DIN EN 10226 RING GAUGE ISO7-2:2000 ve DIN EN 10226 HALKA MASTAR

R ISO 7-2:2000	PITCH HATVE	CODE KOD	EURO
ISO7-2:2000 R 1/8"	28	MISO7R018D	160.00
ISO7-2:2000 R 1/4"	19	MISO7R014D	170.00
ISO7-2:2000 R 3/8"	19	MISO7R038D	205.00
ISO7-2:2000 R 1/2"	14	MISO7R012D	245.00
ISO7-2:2000 R 3/4"	14	MISO7R034D	280.00
ISO7-2:2000 R 1"	11	MISO7R100D	303.00
ISO7-2:2000 R 1-1/4"	11	MISO7R114D	360.00
ISO7-2:2000 R 1-1/2"	11	MISO7R112D	440.00
ISO7-2:2000 R 2"	11	MISO7R200D	500.00
ISO7-2:2000 R 2-1/2"	11	MISO7R212D	540.00
ISO7-2:2000 R 3"	11	MISO7R300D	620.00
ISO7-2:2000 R 4"	11	MISO7R400D	760.00

ISO7-2:2000 parallele ring gauges have go and no go on one single piece.
ISO7-2:2000 düz halka mastarlarda geçer ve geçmez tek parça üzerindedir.



Withworth taper pipe thread ISO7 and DIN EN10226 ring gauges are used for gauging R ISO 7-1 or DIN EN 10226 external taper thread.

ISO 7-2:2000 Ring gauges are parallel and they are marked as "ISO7 R No3"

Withworth konik boru dişi ISO7 ve DIN EN10226 halka mastarlar R ISO 7-1 ve DIN EN 10226 konik dış vida kontrolü için kullanılır. ISO 7-2:2000 Halka mastarlar düzdür "ISO7 R No3" olarak markalanmıştır